

STEAM CLEANER

STEAM CLEANER



INSTRUCTIONS

MAINTENANCE CARD

USER NAME: _____

ADDRESS: _____

TELEPHONE NO: _____

PURCHASE DATE: _____

PRODUCE DATE: _____

DATE OFFACTORY: _____

SERLAL NO: _____

SPARE PART: _____

MOTOR NO: _____

ITEM NO: _____

ITEM SPECIAL NO: _____

CERTIFICATE

1. CABLE	<input checked="" type="checkbox"/>	6. FITTINGS	<input checked="" type="checkbox"/>	11. MANUSAL	<input checked="" type="checkbox"/>
2. CHARGER	<input checked="" type="checkbox"/>	7. SUCTION	<input checked="" type="checkbox"/>	12. PACKING	<input checked="" type="checkbox"/>
3. BATTERIES	<input checked="" type="checkbox"/>	8. CONTROL	<input checked="" type="checkbox"/>	13. QCBY	<input checked="" type="checkbox"/>
4. SWITCH	<input checked="" type="checkbox"/>	9. FUSELAGE	<input checked="" type="checkbox"/>	14. ACCEPTANCE	<input checked="" type="checkbox"/>
5. OUTSIDE	<input checked="" type="checkbox"/>	10. OPERATION	<input checked="" type="checkbox"/>		

The product accords with the technical criteria.

Checker: _____

●INTRODUCTION

To solve the clean cotton fabric sofa or that the party expected the walls, carpet, staircase, car washing and difficult problems in all kinds of fibers, we design the new washing machine as below.

- Spraying and vacuuming synchronistically, it is efficient, flexible and suitable for daily maintenance cleaning.
- With new steam design, you can switch between high temperature steam mode and cold water injection mode at any time.
- It is applicable to all kinds of workplace cleaning, such as sofa, curtains, mattresses, seats, carpets and so on.
- For large area cleaning, the machine is equipped with 15 meters long working radius.
- The Cleaner with powerful suction can dry quickly and clean well. It can be used to absorb dust or water separately.
- The machine can be equipped with steam accessories, the effect of steam for floor/glass/lampblack is remarkable.

●PRINCIPLE

Please read this manual carefully before operating this machine to ensure to operate correctly. If any questions, please contact the local distributors.

- Check whether the power supply voltage matches the nameplate before using it.
- When working, please do not pull the machine with hand brush or suction hose.
- To avoid the machine reversing and the sewage inflow the motor, you could push the base forward or lift the handle to move it directly.
- The sewage fill recovery tank, raising the float ball against the top to stop vacuuming.
- The sewage need to be drained out before continuing to work.
- Clean hand brush and suction hose with water in time to avoid bacteria and odor.
- Take away in-solution tank, install dust bag and filter, connect vacuum nozzle to do vacuuming for small area.
- Do not replace any parts of this product by yourself, otherwise the company will not be liable for any problems.
- This machine is designed for plug-in and instant heating. In order to avoid dry burning, it is necessary to pay attention to the steam ejection when using. Once no steam is ejected, immediately turn off the steam switch, add enough water and restart the machine after cooling for five minutes.

●TECHNICAL DATA

Voltage:220V 50HZ	Airsteam:180m ² /H
Vacuum motor:1000W	Steam motor:2600W
Spray motor:25W*2	Suction hose:4M
Solution tank:4L	Power cord:10M
Recovery tank:12L	Noise Level:≤66dB(A)
Net Weight:14KG	Dimension:36×36×51CM
Gross Weight:20KG	Packing:53×37×65CM

● OPERATION STEP

- 1.Put proper amount of defoamer into recovery tank (A-8).
- 2.Add proper amount of detergent into Solution tank (A-10)with funnel.
- 3.Put infusion tube into in-Solution tank hole and lock side-button(A-6).
- 4.Connect buddy connector (B-11b) to bunghole (A-7).
- 5.Connect remote control (B-12) to hose connector (B-11a).
- 6.Connect steam cube to its inlet connector of remote handle (B-12b).
- 7.Connect acrylic nozzle (B-13) to remote control (B-12) and tied.
- 8.Put steam extend tube (B-16) between remote control(B-12) and big acrylic nozzle (B-15)you need, and screw tightly.
- 9.The machine is equipped with different cleaning tools: sofa nozzle, curtain nozzle and carpet nozzle etc to meet the needs of different workplaces..
- 10.After finish cleaning, please turn off all switches and power supply. Drain out the rest of detergent and water. Place the machine in a dry place.
11. Pay attention to whether red sealing ring is put in place to prevent steam leakage.
- 12.Smart Remote Control, with a water suction switch on top; and a three-position switch below, which includes DRY steam, WET steam, and COLD WATER option.
 VACUUM ——— Strong water absorption
 DRY STEAM ——— Drying quickly
 WET STEAM ——— Wash with water and steam
 COLD WATER ——— Wash with cold water circularly
- 13.Turn on Vacuum switch(A-4) and the sewage is recoverd while steam is coming out.

● DIRECTION

